



8589

REF	PART NO.	QTY	DESCRIPTION	SEE SEC.	NOTES
1	851340	1	Upper gear		
2	832674	1	• Housing		OBSOLETE PART
3	941814	2	• Stud	18205	
4	832667	1	• Gear housing cover		
5	814179	1	• Plug		
6	897682	1	• Gasket		
7	941807	3	• Hex. socket screw		
8	814643	1	• Hollow screw		
9	955989	1	• O-ring		
10	832669	1	• Gasket		
11	839027	1	• Gear set		
12	875425	1	• Bearing box		
13	951940	1	• • Spring pin		
14	183247	1	• • Roller bearing		
15	183668	1	• • Roller bearing		
16	897772	1	• • Oil deflector		EARLY TYPE
17	925256	2	• O-ring		
18	941826	X	• Shim		TH = 0.50mm
	941827	X	• Shim		TH = 0.20mm
	948230	X	• Shim		TH = 0.35mm
19	839253	1	• Sealing ring		
20	914538	1	• Snap ring		
21	832675	1	• Washer		
22	956000	1	• O-ring		
23	943871	X	• Shim		TH = 0,05 MM
	943872	X	• Shim		TH = 0.10mm
	943873	X	• Shim		TH = 0.20mm
24	839028	1	• Joint		
			Bulletin P-44-1-5	P-44-1-5-EN	U-joints
25	853560	1	• • Joint fork kit		
			Bulletin P-44-1-5	P-44-1-5-EN	U-joints
25A	897774	1	• • Fork		REPL BY 853560
			Bulletin P-44-1-5	P-44-1-5-EN	U-joints
25B	853331	2	• • • Lock ring		FOR 853255.
26	839026	1	• • Fork		
27	897706	1	• • Intermediate section		
28	897707	2	• • Cross piece		REPLACED BY 853455., FOR DRIVE UNITS 853452,853453 PZ-29500949.
	853255	2	• • Spider		FOR DRIVE UNITS 853452,853453 PZ29500950-.
29	897776	4	• • • Lock ring		FOR 897707
	853331	4	• • • Lock ring		FOR 853255
30		8	• • • NEEDLE BEARING		
31		8	• • • PROTECTOR RING		
32		8	• • • CORK RING		
33	851293	1	• Screw		OBSOLETE PART
34	839013	1	• Washer		
35	851265	1	• Tensioning ring		
35A	852705	1	• Pivot pin		
35B	941807	2	• Hex. socket screw		
36	956590	4	• Hex. socket screw		
37	942598	4	• Washer		
38	853542	2	• Ball bearing		(183729)
39	832644	2	• Bearing sleeve		
40	943869	X	• Shim		TH = 0,05 MM
	946179	X	• Shim		TH = 0.10mm
	943870	X	• Shim		TH = 0.20mm
41	967352	X	• Shim		TH = 0,05 MM
	943866	X	• Shim		TH = 0.10mm
	943867	X	• Shim		TH = 0.20mm
	943868	X	• Shim		TH = 0.40 mm
42	897385	1	• Shaft		
43	814601	1	• Sliding sleeve		
			Bulletin P-44-1-8	P-44-1-8-EN	Shift mechanism, shift cone and shoe

REF	PART NO.	QTY	DESCRIPTION	SEE SEC.	NOTES
			Bulletin P-44-1-18	P-44-1-18-EN	Shift Cone
44	813970	1	• Spring		
45	26411	1	• Shim		
46	951077	1	• Snap ring		
47	181359	4	• Needle roller assemb		
48	897308	2	• Spacer ring		OBSOLETE PART
49	897313	1	• Spacer ring		
50	897312	2	• Lock ring		
51	839332	1	• Nut		TH = 2,00 MM
	839333	1	• Nut		TH = 2,37 MM
	839334	1	• Nut		TH = 2,65 MM
52	839504	1	• Shift mechanism		
53	839505	1	• • Bearing housing		
54	897816	1	• • Eccentric piston		
			Bulletin P-44-1-7	P-44-1-7-EN	Shift mechanism, eccentric piston
55	814603	1	• • Dog		
56	814184	1	• • Spring		
57	60309	2	• • Ball		OBSOLETE PART, PZ-2829528
58	839136	2	• • Spring		OBSOLETE PART, PZ-2829528
59	941338	X	• • Locking wire		OBSOLETE PART, PZ-2829528, L = 300 MM
60	897711	1	• • Screw		
61	897871	X	• • Shim		TH = 0.2mm
62	958838	1	• • Sealing ring		
63	951924	1	• • Spring pin		
64	942871	1	• • Clevis pin		
65	925093	1	• • O-ring		
66	940169	4	• Hexagon screw		
67	875826	1	• Bellows kit		
		1	• • BELLOWS		
68	853013	1	• • Hose clamp		(961677)
69	853012	1	• • Hose clamp		(961676)
70	839351	1	• Oil dipstick		
71	955974	1	• O-ring		
72	814687	1	• Sign		OBSOLETE PART
73	804269	2	• Drive screw		
74	832570	1	Protecting cover		INCLUDED IN DRIVE UNIT 852411, 852412.
75	897873	1	• Latch		
76	943218	1	• Cross recessed screw		
77	941816	1	Cross recessed screw		INCLUDED IN DRIVE UNIT 852411, 852412.
78	852823	2	Sign		INCLUDED IN DRIVE UNIT 852411, 852412.
79	852824	1	Sign		INCLUDED IN DRIVE UNIT 852411, 852412.