



MS3C

REF	PART NO.	QTY	DESCRIPTION	SEE SEC.	NOTES
2	851673	1	Gear housing		
3	832667	1	Gear housing cover		(832668)
4	956585	3	Screw		
5	814643	1	Hollow screw		
6	955989	1	O-ring	IK	
7	839351	1	Oil dipstick		
8	897682	1	Gasket	IK	
9	943866	X	Adjusting washer		TH = 0,1 MM
	943867	X	Adjusting washer		TH = 0,2 MM
	943868	X	Adjusting washer		TH = 0,4 MM
10	839027	1	Drive gear set		
11	832669	1	Gasket	IK	
12	832644	1	Bearing sleeve		
13	183729	2	Bearing		
14	946179	X	Adjusting washer		TH = 0,1 MM
	943870	X	Adjusting washer		TH = 0,2 MM
15	181359	4	Needle bearing		
16	897308	2	Spacer ring		
17	852371	1	Shaft		
18		1	NUT		
	839332	X	Nut		ALT TH = 2,00 MM
	839333	X	Nut		ALT TH = 2,37 MM
	839334	X	Nut		ALT TH = 2,65 MM
19	850433	1	Lock ring		
20	944522	X	Shim		TH = 0,05 MM
	42981	X	Shim		TH = 0,1 MM
	968057	X	Shim		&TH = 0,2 MM
21	897312	2	Lock ring		
22	850422	1	Spacer ring		
23	852433	1	Wear washer		
24	951077	1	Lock ring		
25	26411	1	Spacer		
26	813970	1	Spring		
	852949	1	Sliding sleeve		PZ 22153-
28	181301	1	Cone		
29	181302	1	Cup		
30	852609	1	Drive gear set		
31	184649	1	Bearing		
32	967352	X	Adjusting washer		TH = 0,05 MM
	941823	X	Adjusting washer		TH = 0,1 MM
	967351	X	Adjusting washer		TH = 0,15 MM
	941824	X	Adjusting washer		TH = 0,2 MM
	967557	X	Adjusting washer		TH = 0,3 MM
	941825	X	Adjusting washer		TH = 0,4 MM
33	852373	1	Bearing cover		
33A	925257	1	O-ring		
34	946472	4	Screw		
35	947084	1	Gasket		(957175)
36	960629	1	Plug		
37	955974	1	O-ring	IK	
38	814179	1	Plug		
39	875425	1	Bearing box		
40	951940	1	· Tensioning din		
41	897772	1	· Oil deflector		
42	183668	1	· Roller bearing		
43	183247	1	· Bearing		
44	925256	2	O-ring	IK	
45	941826	X	Adjusting washer		TH = 0,05 MM
	941827	X	Adjusting washer		TH = 0,2 MM
	948230	X	Shim		TH = 0,35 MM
46	839253	1	Sealing ring	IK	
47	914538	1	Lock ring		
48	832675	1	Washer		

MS3C

REF	PART NO.	QTY	DESCRIPTION	SEE SEC.	NOTES
49	956000	1	O-ring	IK	
50	850276	1	Intermediate section		
51	925257	1	O-ring		
52	965185	6	Flange screw		
53	850275	1	Axle shaft		
54	943871	X	Shim		TH = 0,05 MM
	943872	X	Shim		TH = 0,1 MM
	943873	X	Shim		TH = 0,2 MM
55	839013	1	Washer		
56	851293	1	Screw		
57	851678	1	Bearing housing		
58	946671	6	Flange screw		
59	851496	X	Adjusting washer		TH = 0,1 MM
	851495	X	Adjusting washer		TH = 0,15 MM
	851494	X	Adjusting washer		TH = 0,35 MM
60	925267	1	O-ring	IK	
61	183328	1	Cup		
62	183327	1	Cone		
63	852696	1	Sleeve		
64	852184	X	Shim		TH = 0,05 MM
65	183668	1	Roller bearing		
66	925063	1	O-ring		
67	959026	1	Sealing ring		
68	944530	1	Ring		
69	852368	1	Flange		
70	850471	1	Washer		
71	947855	1	Lock nut		
72	851786	2	Oil cooler		
73	852007	1	Connection pipe		
74	960169	4	• O-ring	IK	
75	851730	1	Connection pipe		
75B	959207	4	Screw		
76	838929	2	• Zinc anod		
77	828928	2	• Nut		
78	959207	4	• Screw		
79	942000	2	• Screw		
80	941906	8	• Spring washer		
81	839504	1	• Shift mechanism		
82	839505	1	• • Bearing housing		
83	814603	1	• • Dog		
84	925093	1	• • O-ring	IK	
85	814184	1	• • Spring		
86	958838	1	• • Sealing ring	IK	
87	897816	1	• • Eccentric piston • • Bulletin P-44-1-7		P-44-1-7-EN Shift mechanism, eccentric piston
88	951924	1	• • Tensioning din		
89	942871	1	• • Pin		
90	897711	1	• • Screw		
91	897871	X	• • Adjusting washer		TH = 0,2 MM
92	852363	1	• Lever		
93	955270	2	• Screw		
94	955781	2	• Nut		
95	955948	2	• Lock washer		
96	804312	1	• Cube		
97	955892	1	• Washer		
98	907834	1	• Cotter pin		(17276)
99	850350	1	• Cable attachment		
100	955273	4	• Screw		
101	819068	1	• Washer		
102	819067	1	• Brace		
103	955246	2	• Screw		
104	946577	2	• Lock nut		
105	940090	2	• Washer		

