



7449

## DRIVE 290

REF	PART NO.	QTY	DESCRIPTION	SEE SEC.	NOTES
1	851340	1	Upper gear unit		INCLUDED IN COMPLETE AQ 290 DRIVE UNIT 853451.
2	832674	1	• Housing		
3	941814	2	• Stud		
4	832667	1	• Gear housing cover		
5	814179	1	• Plug		
6	897682	1	• Gasket	IK	
7	941807	3	• Screw		
8	814643	1	• Hollow screw		
9	955989	1	• O-ring	IK	
10	832669	1	• Gasket	IK	
11	839027	1	• Drive gear set		
12	875425	1	• Bearing box		
13	951940	1	• • Tensioning din		
14	183668	1	• • Roller bearing		
15	183247	1	• Bearing		
16	897772	1	• • Oil deflector		
17	925256	2	• O-ring	IK	
18	941826	X	• Adjusting washer		TH = 0,05 MM
	941827	X	• Adjusting washer		TH = 0,20 MM
	948230	X	• Shim		TH = 0,35 MM
19	853670	1	• Sealing ring	IK	
20	914538	1	• Lock ring		
21	832675	1	• Washer		
22	956000	1	• O-ring	IK	
23	943871	X	• Shim		TH = 0,05 MM
	943872	X	• Shim		TH = 0,10 MM
	943873	X	• Shim		TH = 0,20 MM
24	839028	1	• Joint		
			• Bulletin P-44-1-5	P-44-1-5-EN	U-joints
25	853560	1	• • Joint fork kit		
			• • Bulletin P-44-1-5	P-44-1-5-EN	U-joints
26	839026	1	• • Steering yoke		
27	897706	1	• • Intermediate section		
28	853255	2	• • Cross piece		
29	853331	4	• • • Lock ring		
30		8	• • • NEEDLE BEARING		
31		8	• • • PROTECTOR RING		
32		8	• • • CORK RING		
33	854201	1	• Screw		(851293)
34	839013	1	• Washer		
35	851265	1	• Clamping ring		
35A	852705	1	• Pivot pin		
35B	941807	2	• Screw		
36	956590	4	• Screw		
37	942598	4	• Washer		
38	853542	2	• Ball bearing		(183729)
39	832644	2	• Bearing sleeve		
40	943869	X	• Adjusting washer		TH = 0,05 MM
	946179	X	• Adjusting washer		TH = 0,10 MM
	943870	X	• Adjusting washer		TH = 0,20 MM
41	943252	X	• Adjusting washer		TH = 0,05 MM
	943866	X	• Adjusting washer		TH = 0,10 MM
	943867	X	• Adjusting washer		TH = 0,20 MM
	967557	X	• Adjusting washer		TH = 0,30 MM
	943868	X	• Adjusting washer		TH = 0,40 MM
42	897385	1	• Shaft		
43	814601	1	• Sliding sleeve		
			• Bulletin P-44-1-8	P-44-1-8-EN	Shift mechanism, shift cone and shoe
44	813970	1	• Spring		
45	26411	1	• Spacer		
46	951077	1	• Lock ring		
47	853542	4	• Ball bearing		(183729)
48	897308	2	• Spacer ring		

## DRIVE 290

REF	PART NO.	QTY	DESCRIPTION	SEE SEC.	NOTES
49	897313	1	· Spacer ring		
50	897312	2	· Lock ring		
51	839332	1	· Nut		TH = 2,00 MM
	839333	1	· Nut		TH = 2,37 MM
	839334	1	· Nut		TH = 2,65 MM
52	839504	1	· Shift mechanism		
53	839505	1	· · Bearing housing		
54	897816	1	· · Eccentric piston		
			· · Bulletin P-44-1-7	P-44-1-7-EN	Shift mechanism, eccentric piston
55	814603	1	· · Dog		
56	814184	1	· · Spring		
57	60309	2	· · Ball		PZ-2829528
58	839136	2	· · Spring		PZ-2829528
59	941338	X	· · Locking wire		PZ-2829528 L = 300 MM
60	897711	1	· · Screw		
61	897871	X	· · Adjusting washer		TH = 0,2 MM
62	853868	1	· · Sealing ring	IK	
63	951924	1	· · Tensioning din	IK	
64	942871	1	· · Pin		
65	925093	1	· · O-ring	IK	
66	940169	4	· Screw		
67	875826	1	· Bellows kit		
68	853013	1	· · Hose clamp		
69	853012	1	· · Hose clamp		
70	839351	1	· Oil dipstick		
71	955974	1	· O-ring	IK	
72	814687	1	· Sign		
73	804269	2	· Drive screw		
74	832570	1	Cover		INCLUDED IN COMPLETE AQ 290 DRIVE UNIT 853451.. INCLUDED IN COMPLETE AQ 290 DRIVE UNIT 853459.
75	897873	1	· Latch		
76	943218	1	· Screw		
77	941816	1	Screw		INCLUDED IN COMPLETE AQ 290 DRIVE UNIT 853451.
78	853031	1	Decal		P. INCLUDED IN COMPLETE AQ 290 DRIVE UNIT 853451.
	853030	1	Decal		S.B. INCLUDED IN COMPLETE AQ 290 DRIVE UNIT 853451.
79	853029	1	Decal		INCLUDED IN COMPLETE AQ 290 DRIVE UNIT 853451.