



* = Includes screw, C-10-34231; nut C-11-37164 and neoprene sleeve C-23-32914 for mating white lead wire. Affixed white lead wire required for attaching "start-stop" ignition button switch provided with second station instrument panels B-63178A5 through AB. For start-stop panel replacement parts see Page 21C.
 Page 25C (INSTRUMENTATION) Revised December 1978

				Parts List			
Ref	Class	Part	Description	Qty	Comment	Footnote	
1		32864	PIN CONF. -/X DIM.20 /Y DIM.91/	8			
1		34104	PIN CONF. -/X DIM.20 /Y DIM.10/	8			
1		34101	PIN CONF. -/X DIM.20 /Y DIM.10/	9			
1		36440	PIN CONF. -/X DIM.20 /Y DIM.10/	10			
2		46996 20	PIN CONF.A/X DIM.20 /Y DIM.10	8			
2		39542 20	PIN CONF.A/X DIM.20 /Y DIM.1	8			
2		46801 20	PIN CONF.A/X DIM.20 /Y DIM.12	8			
2		55747 20	PIN CONF.B/X DIM.20 /Y DIM.7	9			
2		55747 45	PIN CONF.B/X DIM.45 /Y DIM.7	9			
2		55790 20	PIN CONF.B/X DIM.20 /Y DIM.12	9			
2		55790 45	PIN CONF.B/X DIM.45 /Y DIM.12	9			
2	84	61705	PIN CONF.C/X DIM.2 /Y DIM.13	9			
2	84	63765	PIN CONF.C/X DIM.2 /Y DIM.13	9			
2		59814 20	PIN CONF.C/X DIM.20 /Y DIM.12	9			
3	84	64836	PIN CONF.C/X DIM.2 /Y DIM.13	9			
4	84	62029w1	PIN CONF.C/X DIM.2 /Y DIM.15	16			
4	84	62029w1	PIN CONF.C/X DIM.2 /Y DIM.15	16			
4	84	62029	PIN CONF.C/X DIM.2 /Y DIM.15	16			
4	84	62029	PIN CONF.C/X DIM.2 /Y DIM.15	16			
4	84	63701	PIN CONF.C/X DIM.2 /Y DIM.15	16			
4	84	63701	PIN CONF.C/X DIM.2 /Y DIM.15	16			
4	84	63701	PIN CONF.C/X DIM.2 /Y DIM.15	16			
4	84	63701	PIN CONF.C/X DIM.2 /Y DIM.15	16			
4	84	63701	PIN CONF.C/X DIM.2 /Y DIM.15	16			
5	84	64837	PIN CONF.C/X DIM.2 /Y DIM.15	16			
5	84	64837	PIN CONF.C/X DIM.2 /Y DIM.15	16			
5	84	64837	PIN CONF.C/X DIM.2 /Y DIM.15	16			
6	84	63446	PIN CONF.D-MALE/X DIM.2 /Y C 3	3			
6	84	63445	PIN CONF.D-FEMALE/X DIM.1 /Y 3	3			
7	84	74028A 3	PIN CONF.C/X DIM.3 /Y DIM 14'	14			
7	84	74028A15	PIN CONF.C/X DIM.15 /Y DIM 14'	14			
7	84	74028A20	PIN CONF.C/X DIM.20 /Y DIM 14'	14			
7	84	74028A25	PIN CONF.C/X DIM.25 /Y DIM 14'	14			
7	84	87005A 3	PIN CONF.C/X DIM.3 /Y DIM 14'	14			
7	84	87005A20	PIN CONF.C/X DIM.20 /Y DIM 14'	14			
7	84	87005A25	PIN CONF.C/X DIM.25 /Y DIM 14'	14			