



IMPORTANT: ALL EYELET ELECTRICAL CONNECTIONS SHOULD BE COATED WITH LIQUID NEOPRENE AFTER RESPECTIVE SCREW, BOLT OR NUT IS TIGHTENED.

**Quicksilver Lubrication/Sealant Application Points**

 Liquid Neoprene (92-25711-2)

**Parts List**

Ref	Class	Part	Description	Qty	Comment	Footnote
-		13541	PLUG-FEMALE WIRES	2		
1		44331 4	IGNITION PLATE	1		
2	332	5772A 7	SWITCH BOX ASSEMBLY	1		
3	11	45076	NUT	13		
4	10	40011110	SCREW	4		
5	54	63153	J-CLIP	1		
6	84	43442A 3	PRIMARY HARNESS ASSEMBLY	1		
7	33	816737 2	SPARK PLUG (NGK #BP8H-N-10)	4		
7	33	816837 2	SPARK PLUG (CAN/BEL-NGK#BF	4		
8	84	813715A 8	HIGH TENSION CABLE	1	(S/N-USA-0G301750/BEL-988550)	
8	84	821945A57	HIGH TENSION CABLE	1	(S/N-USA-0G301751/BEL-988550)	
9	85	63709A 1	PROTECTOR	4		
10		815279T	VOLTAGE REGULATOR	1		
11	10	40106 35	SCREW	2		
12	339	832757A 4	IGNITION COIL ASSEMBLY	4		
13	11	45076	NUT	8		
14		87554	COVER	1		
15	10	40007114	SCREW	5		
16	12	89302	WASHER	5		
17	84	821546A 3	HARNESS	1		
18	84	824912A 3	CABLE (6-1/2 IN.)	1		
18	84	824912A 4	CABLE (4-3/4 IN.)	1		
19	10	40007107	SCREW	2	USE WHERE APPLICABLE	
20	11	45076	NUT	3	USE WHERE APPLICABLE	
21		17602A 2	TERMINAL BLOCK	1	USE WHERE APPLICABLE	
22	10	821550 25	SCREW	4		
23		45915	TERMINAL BLOCK	2		
24	10	48408	SCREW	4		
25	84	43443A 9	ENGINE WIRING HARNESS	1		
26	88	79091	FUSE (20 AMP)	1		
27	84	88439A 3	BATTERY CABLE	1	(POSITIVE)	
27	84	88439A 4	BATTERY CABLE	1	(NEGATIVE)	
28		13550T 1	COVER	1		
29	10	40007114	SCREW (50 MM)	3		
29	10	40011110	SCREW (30 MM)	1		
30	89	817109A 2	STARTER SOLENOID	1		
31	23	818968	BUSHING	2		
32	10	40011109	SCREW	2		
33	12	40023 14	WASHER	2		
34	84	88807A 6	WIRE (BLACK)	AR		9
35	84	82279A 24	WIRE (USE WHERE APPLICABLE)	1	(REF. 4.1 (A))	