



19262

| Parts List | | | | | | |
|------------|-------|----------|--------------------------------|-----|---------------------|----------|
| Ref | Class | Part | Description | Qty | Comment | Footnote |
| 1 | 462 | 8839A 2 | CRANKSHAFT ASSEMBLY | 1 | | |
| 2 | 30 | 64424 | BEARING, BALL - LOWER AND | 2 | | |
| 3 | 15 | 22369A 1 | SHIM, LOWER BEARING TO CRA | AR | | |
| 4 | 542 | 7509A 3 | MAIN BEARING ASSEMBLY (VAL) | 2 | | |
| 5 | 17 | 20032 | DOWELL PIN, MAIN BEARING | 4 | | |
| 6 | 17 | 60282 | PIN, Dowel (STEPPED) | 2 | | |
| 7 | 17 | 65855 | PIN, Dowel, REED STOP | 16 | | |
| 8 | 34 | 66051A 1 | REED SET, MATCHED - MAIN B | 2 | | |
| 9 | 34 | 65946 | REED STOP | 8 | | |
| 10 | 10 | 77280 | SCREW, (.190-32 X .56), REED | 8 | | |
| 11 | 11 | 20110 | NUT, (#10-32), REED STOP MO | 8 | | |
| 12 | 10 | 38055 | SCREW, (.190-32 X .62), MAIN B | 4 | | |
| 13 | 11 | 20110 | NUT, (#10-32), MAIN BEARING | 4 | | |
| 14 | | 26113 | RACE, OUTER (PAIR) | 2 | | |
| 15 | 53 | 26933 | SNAP RING, SNAP - OUTER F | 2 | | |
| 16 | 29 | 71422 | NEEDLE BEARING | 112 | | |
| 17 | 774 | 8600A 3 | PISTON/PISTON PIN | 3 | (Standard)(50) | |
| 17 | 774 | 9095A 1 | PISTON/PISTON PIN | AR | (.015 Oversize)(50) | |
| 17 | 774 | 9096A 1 | PISTON/PISTON PIN | AR | (.030 Oversize)(50) | |
| 17 | 776 | 8896A 3 | PISTON/PISTON PIN | 3 | (Standard)(60) | |
| 17 | 776 | 8897A 2 | PISTON/PISTON PIN | AR | (.015 Oversize)(60) | |
| 17 | 776 | 8898A 2 | PISTON/PISTON PIN | AR | (.030 Oversize)(60) | |
| 18 | 40 | 52035 | RING, Lock, PISTON PIN | 6 | | |
| 19 | 39 | 78816A12 | RING, PISTON | 1 | (STANDARD) | |
| 19 | 39 | 78811A12 | RING, PISTON | AR | (.015 Oversize) | |
| 19 | 39 | 88392A12 | RING | AR | (.030 Oversize) | |
| 20 | 624 | 8101A 3 | CONNECTING ROD AND CAP AS: | 3 | | |
| 21 | 10 | 91012 | SCREW, (.25-28), CAP TO CONN | 6 | | |
| 22 | 31 | 62596A 1 | BEARING ASSEMBLY | 3 | | |
| 23 | 29 | 47270 | BEARING, NEEDLE - PISTON PI | 87 | | |
| 24 | 12 | 47247 | WASHER, NEEDLE LOCATING | 6 | | |