



Quicksilver Lubrication/Sealant  
 Application Points

-  Loctite 271 (Obtain Locally)
-  Loctite Primer "T" (92-59327-1)

**A** - DO NOT touch this adjustment. This is preset by the manufacturer and is NOT for field service.  
 Conventional carb cleaners will not affect the sealant securing this adjustment

Parts List

Ref	Class	Part	Description	Qty	Comment	Footnote
1	3301	821679A23	CARBURETOR (TOP)	1	75 MANUAL-WME-47	
1	3301	821679A24	CARBURETOR (CENTER)	1	75 MANUAL-WME-47	
1	3301	821679A25	CARBURETOR (BOTTOM)	1	75 MANUAL-WME-47	
1	3301	821679A20	CARBURETOR (TOP)	1	75 ELECTRIC-WME-46	
1	3301	821679A21	CARBURETOR (CENTER)	1	75 ELECTRIC-WME-46	
1	3301	821679A22	CARBURETOR (BOTTOM)	1	75 ELECTRIC-WME-46	
1	3301	821679A26	CARBURETOR (TOP)	1	75 ELECTRIC-WME-48 NON -OIL	
1	3301	821679A27	CARBURETOR (CENTER)	1	75 ELECTRIC-WME-48 NON -OIL	
1	3301	821679A28	CARBURETOR (BOTTOM)	1	75 ELECTRIC-WME-48 NON -OIL	
1	3301	821946A30	CARBURETOR (TOP)	1	90-WME-49	
1	3301	821946A31	CARBURETOR (CENTER)	1	90-WME-49	
1	3301	821946A32	CARBURETOR (BOTTOM)	1	90-WME-49	
2	27	15172 3	GASKET-FLANGE	3		4,6
3	10	F10155	SCREW-THROTTLE VALVE	6		5
4	1395	9724 2	THROTTLE VALVE	3	(WME-29/30/31/41)	
4	1395	9724 4	THROTTLE VALVE	3	(WME-46/47/48/49)	
5			RETAINING RING	3		5
6		F10064	FLOAT SHAFT	3		5
7	1395	823632 2	THROTTLE SHAFT (CENTER)	1		
8	1395	823634	SCREW-LEVER ADJUSTMENT	2		
9	1395	811220	SCREW	6		
10	1395	811221	COVER PLATE	3		
11			GASKET-COVER PLATE	3		5,6
12			SPRING-IDLE NEEDLE	3		5
13			IDLE NEEDLE	2		5
14	1395	8423	JET (.094)	3	(WME-29)	
15	1395	823632	THROTTLE SHAFT (UPPER/LO	2		
16			SPRING-THROTTLE RETURN	3		5
17	1395	808738	GASKET-NOZZLE WELL	3		5
18			GASKET-FUEL BOWL	3		5,6
19	1395	9595 1	INLET NEEDLE VALVE	3		5,1
20	1395	9594	FLOAT	3		
21	1395	811695	FUEL BOWL (UPPER)	1	(WME-30/46/47/49)	
21	1395	811696	FUEL BOWL (UPPER)	1	(WME-29/31/41/48)	
21	1395	811693	FUEL BOWL (CENTER/LOWER	2		
22	1395	808612	SCREW-FUEL BOWL	12		
23	1395	811694	PLUG	3		
24	1395	802731	SEAL (CONSISTS OF 4 SEALS	1		5
25	1395	6028	MAIN FUEL JET (.050)	AR	(75)	11
25	1395	6359	MAIN FUEL JET (.052)	AR	(75)	11
25	1395	6325	MAIN FUEL JET (.054)	AR	(75)	11