



Quicksilver Lubrication/Sealant Application Points

 Liquid Neoprene (92-25711-2)

IMPORTANT: All eyelet electrical connections should be coated with LIQUID NEOPRENE after respective screw, bolt or nut is tightened

Parts List						
Ref	Class	Part	Description	Qty	Comment	Footnote
1		821546A	3 HARNESS	1		
2	84	18495A26	SWITCH BOX	1		1
3	10	822393	12 SCREW (M5 X 12)	1		
4	10	40011110	SCREW (M5 X .8 X 30)	3		
5		854515	VOLTAGE REGULATOR	1		1
6	10	40106	35 SCREW	2		
7	89	817109A	2 STARTER SOLENOID	1		
8	23	818968	BUSHING	2		
9	11	26419	NUT (8-32)	2		
10	10	40011109	SCREW	2		
11	12	40023	14 WASHER	2		
12	84	88807A	6 WIRE (BLACK - 3-1/2 IN.)(USE WT	1		
12	84	88807A39	WIRE (BLACK - 5 IN.)	1		
12	84	88807A40	WIRE (BLACK - 6 IN.)	1		
12	84	79139A	2 WIRE (RED - 7-1/2 IN.)(USE WHE	1		
13	13	53166	LOCKWASHER (5/16 IN.)	2		
14	11	68292	NUT (5/16-8)	2		
15	10	821550	25 SCREW	3		
16	84	813715A	7 HIGH TENSION CABLE	1		
17	85	63709A	1 PROTECTOR	3		
18	33	97182	SPARK PLUG (NGK #BUHW-2):	3		
18	33	14103570	SPARK PLUG (BELGIUM/CANAI	3		
18	33	14103550	SPARK PLUG (BELGIUM/CANAI	3		
19		826819	2 IGNITION PLATE	1		
20	84	824912A	2 CABLE-IGNITION COIL (BLACK - 7	1		
20	84	824912A	1 CABLE-IGNITION COIL (BLACK - 3	1		
21	339	832757A	4 IGNITION COIL ASSEMBLY	3		1
22	11	45076	NUT	6		
23		17602A	2 RECTIFIER	1		
24	10	40007107	SCREW	2		
25	11	45076	NUT	2		
26		43542	COVER	1		
27	10	40007115	SCREW	6		
28	12	89302	WASHER	6		
29		826820	COVER	1		
30	10	40011110	SCREW (M5 X .08 X 30)	3		
31	84	88439A	3 BATTERY CABLE	1	(POSITIVE)	
31	84	88439A11	BATTERY CABLE	1	(POSITIVE-ELEC.-NON/OIL)	
31	84	88439A	4 BATTERY CABLE	1	(NEGATIVE)	
32		45315	1 TERMINAL BLOCK	1	DOUBLE QTY.'S FOR ELECTRIC	
32	10	48408	2 SCREW	2	DOUBLE QTY.'S FOR ELECTRIC	