



March Pump Parts




FIG 1MMC

MODEL 2CP MD & LC 2CP MD

No.	Each	Description
125-007-10	\$1.30	Cooling Tube Seal
125-113-01	14.40	Pump Mounting Base w/ Grommets (Neoprene 2 Req.)
125-055-01	22.45	Impeller & Magnetic Assy.
125-061-10	12.00	Impeller Shaft (Ceramic)
125-065-10	5.10	Cover O-Ring (Viton)
125-071-10	4.00	Bracket Gasket (Neoprene)
130-028-10	5.30	Thrust Washer (Ceramic)

MODEL 3CP MD & LC 3CP MD

No.	Each	Description
125-007-10	\$1.30	Cooling Tube Seal (Neoprene 2 Req.)
125-113-01	14.40	Pump Mounting Base w/ Grommets
130-006-10	32.05	Impeller Spindle
130-008-01	32.05	Impeller & Magnet Assy. (Old Style) Strt. Blk. Blades
130-011-10	3.20	Cover O-Ring (Buna N)
130-012-10	3.20	Bracket O-Ring (Buna N)
130-020-01	25.65	Impeller Assembly (New Style) Curved White Blades
130-024-10	13.65	Impeller Spindle
130-025-10	3.20	Bracket O-Ring
130-028-10	5.30	Thrust Washer (Ceramic)
135-040-10	0.65	Spindle Screw
135-041-10	3.20	Spindle O-Ring (Viton)
135-044-10	0.65	Support Washer
410-009-10	0.32	Washer (Polypropylene)

MODEL AC 5C MD & LC5CMD

No.	Each	Description
130-024-10	\$13.65	Spindle (Ceramic)
130-028-10	5.30	Thrust Washer (Ceramic)
135-007-10	3.20	O-Ring (Buna N)
150-020-10	8.05	Quad. Ring for Motor Bracket
150-030-01	30.45	Impeller & Magnet Assy.
150-032-10	12.85	Pump Head Cover
150-153-01	32.05	Pump Housing - LC5CMD



originators of the

SEAL-LESS MAGNETIC DRIVE PUMP

offers the ultimate in reliable, trouble-free performance for chemical, OEM, industrial, hydronic, and solar applications

Check these advanced features:

- Leak-proof, seal-less magnetic drive
- Friction-free operation for reduced power consumption
- Magnetic coupling acts as a clutch to provide overload protection
- Broad range of construction materials for most corrosive solutions
- Easy-to-service without special tools
- Over 150 stocking sales and service locations worldwide

