



10029

DRIVE DP-A

REF	PART NO.	QTY	DESCRIPTION	NOTES
1	854049	1	Gear under	RATIO 1,78:1. REPLACED BY LOWER GEAR UNIT 854485 AND SPLINE SLEEVE 854553.
2	854051	1	· Housing	
3	854053	1	· · Bearing housing	
4	852643	2	· · Attaching plate	
5	948338	6	· · Pop rivet	
6	852644	1	· · Check valve	
7	854054	1	· Steering fin	
8	941817	1	· Screw	
8A	852183	1	· Countershaft	REPL BY 854611
9	854611	1	· Intermedi.shaft kit	
9A	184682	1	· · Cone	IK FOR 854611
9B	969071	1	· · Round nut	FOR 854611
9C	854533	1	· · Cover	FOR 854611
10	184654	1	· Needle bearing	
11	184682	1	· Cone	FOR 852183
12	853532	1	· Gear set	RATIO 1,78:1
13	852212	1	· Nut	IK
14	941832	X	· Adjusting washer	TH = 0,05 MM
	941833	X	· Adjusting washer	TH = 0,20 MM
15	183374	1	· Ball bearing	
16	944970	X	· Adjusting washer	
17	11072	1	· Roller bearing	
18	944522	X	· Shim	TH = 0,05 MM
	42981	X	· Shim	TH = 0,10 MM
	968057	X	· Shim	TH = 0,20 MM
	42980	X	· Shim	TH = 0,35 MM
19	897387	1	· Spacer ring	
20	907023	1	· Lock washer	IK
21	906633	1	· Nut	IK FOR 852183
22	814482	1	· Oil pump screen	
23	852904	1	· Magnetic plug	
24	955974	1	· O-ring	IK
25	852181	1	· Driveshaft	
25A	11044	1	· Bearing	
26	184765	1	· Roller bearing, COMPL.	
26A	184690	1	· · Bearing	REPL BY 184765
27	184689	1	· · Cup	REPL BY 184765
28	967352	X	· Adjusting washer	TH = 0,05 MM
	941823	X	· Adjusting washer	TH = 0,10 MM
	967351	X	· Adjusting washer	TH = 0,15 MM
	941824	X	· Adjusting washer	TH = 0,20 MM
	941825	X	· Adjusting washer	TH = 0,40 MM
29	184691	1	· Bearing	
30	81374	X	· Adjusting washer	TH = 0,10 MM
				REPL BY 191834
	81375	X	· Adjusting washer	TH = 0,15 MM
				REPL BY 191835
	81376	X	· Adjusting washer	TH = 0,35 MM
				REPL BY 191837
30A	191834	X	· Shim	TH = 0,10 MM
	191835	X	· Shim	TH = 0,15 MM
	191837	X	· Shim	TH = 0,25 MM
31	925258	2	· O-ring	IK
32	941812	2	· Screw	
33	875821	1	· Zinc ring kit	
34	966808	2	· · Screw	
35	183859	1	· Needle bearing	
36	184683	1	· Cone	
37	851407	2	· Sealing ring	IK
38	853440	1	· Line cutter	(852198) FRONT

