



| REF | PART NO. | QTY | DESCRIPTION | SEE SEC. | NOTES |
|-----|----------|-----|----------------------------|-------------|--|
| 1 | | 1 | | | INCLUDED IN FOLDING PROPELLER., REPLACED BY 1EA 814598 1EA 814601 1EA 814603., PZ-2890112 |
| | 850460 | 1 | Upper gear | | EARLY TYPE OF SPLINE SLEEVE IS REPLACED BY SHAFT 852527 + SPLINE SLEEVE 852534., REPLACED BY 1EA 814598 1EA 814601 1EA 814603., PZ-2898014 |
| | 851340 | 1 | Upper gear | | REPLACED BY 850788., PZ2898015- |
| 2 | | 1 | · Housing | | |
| 3 | 941814 | 2 | · Stud, SCREW | 12918 | |
| | | | | 12919 | |
| 4 | 832667 | 1 | · · Gear housing cover | | |
| 5 | 814179 | 1 | · · Plug | | |
| 6 | 897682 | 1 | · · Gasket | | |
| 7 | 941807 | 3 | · · Hex. socket screw | | |
| 8 | 814643 | 1 | · · Hollow screw | | |
| 9 | 955989 | 1 | · · O-ring | | |
| 10 | 832669 | 1 | · · Gasket | | |
| 11 | 839027 | 1 | · · Gear set | | |
| 12 | 875425 | 1 | · · Bearing box | | |
| 13 | 951940 | 1 | · · · Spring pin | | |
| 14 | 183247 | 1 | · · · Roller bearing | | |
| 15 | 183668 | 1 | · · · Roller bearing | | |
| 16 | 897772 | 1 | · · · Oil deflector | | |
| 17 | 925256 | 2 | · · O-ring | | |
| 18 | 941826 | X | · · Shim | | TH = 0.50mm |
| | 941827 | X | · · Shim | | TH = 0.2mm |
| | 948230 | X | · · Shim | | TH = 0.35mm |
| 19 | 839253 | 1 | · · Sealing ring | | |
| 20 | 914538 | 1 | · · Snap ring | | |
| 21 | 832675 | 1 | · · Washer | | |
| 22 | 956000 | 1 | · · O-ring | | |
| 23 | 943871 | X | · · Shim | | TH = 0,05 MM |
| | 943872 | X | · · Shim | | TH = 0.1mm |
| | 943873 | X | · · Shim | | TH = 0.2mm |
| 24 | 839028 | 1 | · · Joint | | |
| | | | Bulletin P-44-1-5 | P-44-1-5-EN | U-joints |
| 25 | 897774 | 1 | · · · Fork | | |
| | | | Bulletin P-44-1-5 | P-44-1-5-EN | U-joints |
| 26 | 839026 | 1 | · · · Fork | | |
| 27 | 897706 | 1 | · · · Intermediate section | | |
| 28 | 897707 | 2 | · · · Cross piece | | |
| 29 | 897776 | 4 | · · · · Lock ring | | |
| 30 | | 8 | · · · · NEEDLE BEARING | | |
| 31 | | 8 | · · · · PROTECTOR RING | | |
| 32 | | 8 | · · · · CORK RING | | |
| 33 | | 1 | · · Screw | | (945090) |
| 34 | 839013 | 1 | · · Washer | | |
| 35 | 832573 | 1 | · · Tensioning ring | | INCLUDED IN FOLDING PROPELLER., PZ-2890112 |
| | | 1 | · · Tensioning ring | | EARLY TYPE OF SPLINE SLEEVE IS REPLACED BY SHAFT 852527 + SPLINE SLEEVE 852534., PZ-2898014 |
| | 851265 | 1 | · · Tensioning ring | | REPLACED BY 850788., PZ2898015- |
| 35A | 852705 | 1 | · · Pivot pin | | (851263) PZ2898015- |
| 35 | | | | | REPL BY 852705 |
| 35B | 941807 | 2 | · · · Hex. socket screw | | PZ2898015- |
| 36 | 956590 | 4 | · · · Hex. socket screw | | |
| 37 | 942598 | 4 | · · · Washer | | |
| 38 | 183729 | 2 | · · · Ball bearing | | |
| 39 | 832644 | 2 | · · · Bearing sleeve | | |
| 40 | 943869 | X | · · · Shim | | TH = 0,05 MM |
| | 946179 | X | · · · Shim | | TH = 0.1mm |
| | 943870 | X | · · · Shim | | TH = 0.2mm |
| 41 | 943866 | X | · · · Shim | | TH = 0.1mm |
| | 943867 | X | · · · Shim | | TH = 0.2mm |
| | 943868 | X | · · · Shim | | TH = 0.4mm |
| 42 | 897385 | 1 | · · · Shaft | | |

| REF | PART NO. | QTY | DESCRIPTION | SEE SEC. | NOTES |
|-----|----------|-----|----------------------------|--------------|---|
| 43 | 814601 | 1 | · · · Sliding sleeve | | |
| | | | Bulletin P-44-1-8 | P-44-1-8-EN | Shift mechanism, shift cone and shoe |
| | | | Bulletin P-44-1-18 | P-44-1-18-EN | Shift Cone |
| 44 | 813970 | 1 | · · · Spring | | |
| 45 | 26411 | 1 | · · · Shim | | |
| 46 | 951077 | 1 | · · · Snap ring | | |
| 47 | 181359 | 4 | · · · Needle roller assemb | | |
| 48 | | 2 | · · · Spacer ring | | |
| 49 | 897313 | 1 | · · · Spacer ring | | |
| 50 | 897312 | 2 | · · · Lock ring | | |
| 51 | 839332 | 1 | · · · Nut | | TH = 2,00 MM ALT |
| | 839333 | 1 | · · · Nut | | TH = 2,37 MM ALT |
| | 839334 | 1 | · · · Nut | | TH = 2,65 MM ALT |
| 52 | 839504 | 1 | · · · Shift mechanism | | |
| 53 | 839505 | 1 | · · · Bearing housing | | |
| 54 | 897816 | 1 | · · · Eccentric piston | | |
| | | | Bulletin P-44-1-7 | P-44-1-7-EN | Shift mechanism, eccentric piston |
| 55 | 814603 | 1 | · · · Dog | | |
| 56 | 814184 | 1 | · · · Spring | | |
| 57 | | 2 | · · · Ball | | PZ-2829528 |
| 58 | | 2 | · · · Spring | | PZ-2829528 |
| 59 | | X | · · · Locking wire | | PZ-2829528 L = 300 MM |
| 60 | 897711 | 1 | · · · Screw | | |
| 61 | 897871 | X | · · · Shim | | TH = 0.2mm |
| 62 | 958838 | 1 | · · · Sealing ring | | (941866) |
| 63 | 951924 | 1 | · · · Spring pin | | |
| 64 | 942871 | 1 | · · · Clevis pin | | |
| 65 | 925093 | 1 | · · · O-ring | | |
| 66 | 940169 | 4 | · · Hexagon screw | | |
| 67 | 875256 | 1 | · · Bellows | | |
| 68 | 961677 | 1 | · · Hose clamp | | |
| 69 | 961676 | 1 | · · Hose clamp | | |
| 70 | 839351 | 1 | · · Oil dipstick | | |
| 71 | 955974 | 1 | · · O-ring | | |
| 72 | | 1 | · · Sign | | |
| 73 | 804269 | 2 | · · Drive screw | | |
| 74 | 832716 | 1 | Shoulder screw | | INCLUDED IN FOLDING PROPELLER., PZ-2890112 1/2" |
| | 839696 | 1 | Shoulder screw | | EARLY TYPE OF SPLINE SLEEVE IS REPLACED BY SHAFT 852527 + SPLINE SLEEVE 852534., PZ-2898014 M18 |
| 75 | 832570 | 1 | Protecting cover | | |
| 76 | 897873 | 1 | · Latch | | |
| 77 | 943218 | 1 | · Cross recessed screw | | |
| 78 | 941816 | 1 | Cross recessed screw | | |
| 79 | 839465 | 1 | Sign | | |