



5070

REF	PART NO.	QTY	DESCRIPTION	SEE SEC.	NOTES
1		1	Upper gear		
2		1	• Gear housing		
3		1	• • Gear housing cover		
4		1	• • • Screw		EARLY TYPE
5	804344	1	• • • Gasket		EARLY TYPE
6	832573	1	• • Tensioning ring		
7		1	• GEAR SET WITH BRONZE CONE		EARLY TYPE OF UPPER GEAR 852488 IS REPLACED BY UPPER GEAR 852536 + SPLINE SLEEVE 852534., PZ-2510624
		1	• • Gear set, SET OF GEARS STEEL CONE		PZ2510625-
8	183458	2	• • • Ball bearing		
9		2	• • • Bearing sleeve		
10		X	• • • Adjusting washer		TH = 0,05 MM
		X	• • • Adjusting washer		TH = 0.20mm
11	897312	2	• • • Lock ring		
12	897313	1	• • • Spacer ring		
13		2	• • • Spacer ring		
14	181359	4	• • • Needle roller assemb		
15	914459	1	• • • Snap ring		
16	26411	1	• • • Shim		
17	813970	1	• • • Spring		
18		1	• • • Sliding sleeve, SLIDING SLEEVE OF STEEL		PZ-2510624
	814601	1	• • • • Sliding sleeve, SLIDING SLEEVE OF BRONZE		PZ2510625-
			Bulletin P-44-1-8	P-44-1-8-EN	Shift mechanism, shift cone and shoe
			Bulletin P-44-1-18	P-44-1-18-EN	Shift Cone
18					
19		1	• • • • • SHAFT		INCLUDED IN DRIVE UNIT 120S.
20	814168	1	• • • • • Gasket		
21	839332	1	• • • • • Nut		TH = 2,00 MM ALT
	839333	1	• • • • • Nut		TH = 2,37 MM ALT
	839334	1	• • • • • Nut		TH = 2,65 MM ALT
22	941823	X	• • • • • Shim		TH = 0.10mm
	941824	X	• • • • • Shim		TH = 0.20mm
	941825	X	• • • • • Shim		TH = 0.40 mm
23	941807	3	• • • • • Hex. socket screw		
24		1	• • • • • Hollow screw		PZ-2514280
	814643	1	• • • • • Hollow screw		PZ2514281-
25	804261	1	• • • • • Gasket		PZ-2514280
	955989	1	• • • • • O-ring		PZ2514281-
26	839351	1	• • • • • Oil dipstick		
27	804261	1	• • • • • Gasket		PZ-2785179
	955974	1	• • • • • O-ring		PZ2785180-
28		1	• • • • • Hex. socket screw		
29		1	• • • • • Washer		
30		X	• • • • • Adjusting washer		TH = 0,05 MM
		X	• • • • • Adjusting washer		TH = 0.10mm
		X	• • • • • Adjusting washer		TH = 0.20mm
31		1	• • • • • Sign		
32	804269	2	• • • • • Drive screw		
33	925256	2	• • • • • O-ring		
34		1	• • • • • DOUBLE BEARING UNIT		INCLUDED IN LOWER GEAR UNIT 852487., PZ-2512320
	875425	1	• • • • • Bearing box		PZ2512321-
35	951940	1	• • • • • Spring pin		
36	183668	1	• • • • • Roller bearing		PZ2512321-
37	183247	1	• • • • • Roller bearing		PZ2512321-
38	897772	1	• • • • • Oil deflector		
39	941826	X	• • • • • Shim		TH = 0,05 MM
	941827	X	• • • • • Shim		TH = 0.20mm

REF	PART NO.	QTY	DESCRIPTION	SEE SEC.	NOTES
40	942615	1	• • • • • Sealing ring		PZ-2512320 D = 72 MM
	839253	1	• • • • • Sealing ring		PZ2512321- D = 75 MM
41	914537	1	• • • • • Snap ring		PZ-2512320
	914538	1	• • • • • Snap ring		PZ2512321-
42		1	• • • • • Washer		
43	956000	1	• • • • • O-ring		
44	956590	4	• • • • • Hex. socket screw		
45	942598	4	• • • • • Washer		
46		1	• • • • • Shift mechanism, GEAR MECHANISM SLIDING SHOE OF BRONZE		PZ-2510624
	839504	1	• • • • • Shift mechanism, SHIFT MECHANISM SLIDING SHOE OF BRONZE		PZ2510625-
47	839505	1	• • • • • • • • Bearing housing		
48	897816	1	• • • • • • • Eccentric piston		
			Bulletin P-44-1-7	P-44-1-7-EN	Shift mechanism, eccentric piston
49	897871	X	• • • • • • • Shim		TH = 0.20mm
50	897711	1	• • • • • • • Screw		
51	942871	1	• • • • • • • Clevis pin		
52	951924	1	• • • • • • • Spring pin		
53	958838	1	• • • • • • • Sealing ring		(941866)
54		2	• • • • • • • Ball		EARLY TYPE
55		2	• • • • • • • Spring		EARLY TYPE
56		X	• • • • • • • Locking wire		EARLY TYPE L = 300 MM
57	814184	1	• • • • • • • Spring		
58	925093	1	• • • • • • • O-ring		
59	897715	1	• • • • • • • Dog		PZ-2510624
	814603	1	• • • • • • • Dog		PZ2510625-
60	940169	4	Hexagon screw		
61		1	Joint		
62	897774	1	• Fork		
			Bulletin P-44-1-5	P-44-1-5-EN	U-joints
63		1	• Fork		
64	897706	1	• Intermediate section		
65	897707	2	• Cross piece		
66	897776	4	• • Lock ring		
67		8	• • NEEDLE BEARING		
68		8	• • CORK RING		
69		8	• • PROTECTOR RING		
70	961677	1	Hose clamp		
71	875256	1	Bellows		
72	961676	1	Hose clamp		
73	897456	1	Shoulder screw		
74	832570	1	Protecting cover		
75	897873	1	• Latch		
76	943218	1	• Cross recessed screw		
77	941816	1	Cross recessed screw		
78		1	Sign		