



7449

REF	PART NO.	QTY	DESCRIPTION	SEE SEC.	NOTES
1	851340	1	Upper gear		INCLUDED IN COMPLETE AQ 290 DRIVE UNIT 853451.
2		1	· Housing		
3	941814	2	· Stud		
4	832667	1	· Gear housing cover		
5	814179	1	· Plug		
6	897682	1	· Gasket		
7	941807	3	· Hex. socket screw		
8	814643	1	· Hollow screw		
9	955989	1	· O-ring		
10	832669	1	· Gasket		
11	839027	1	· Gear set		
12	875425	1	· Bearing box		
13	951940	1	· · Spring pin		
14	183247	1	· · Roller bearing		
15	183668	1	· Roller bearing		
16	897772	1	· · Oil deflector		EARLY TYPE
17	925256	2	· O-ring		
18	941826	X	· Shim		TH = 0,05 MM
	941827	X	· Shim		TH = 0.20mm
	948230	X	· Shim		TH = 0.35mm
19	839253	1	· Sealing ring		
20	914538	1	· Snap ring		
21	832675	1	· Washer		
22	956000	1	· O-ring		
23	943871	X	· Shim		TH = 0,05 MM
	943872	X	· Shim		TH = 0.10mm
	943873	X	· Shim		TH = 0.20mm
24	839028	1	· Joint		
			Bulletin P-44-1-5	P-44-1-5-EN	U-joints
25	853560	1	· · Joint fork kit		
			Bulletin P-44-1-5	P-44-1-5-EN	U-joints
26	839026	1	· · Fork		
27	897706	1	· · Intermediate section		
28	897707	2	· · Cross piece		REPLACED BY 853455., PZ-29002858
	853255	2	· · Spider		PZ29002859-
29	897776	4	· · · Lock ring		FOR 897707
	853331	4	· · · Lock ring		FOR 853255.
30		8	· · · NEEDLE BEARING		
31		8	· · · PROTECTOR RING		
32		8	· · · CORK RING		
33		1	· Screw		
34	839013	1	· Washer		
35	851265	1	· Tensioning ring		
35A	852705	1	· Pivot pin		
35B	941807	2	· Hex. socket screw		
36	956590	4	· Hex. socket screw		
37	942598	4	· Washer		
38		2			(183729)
39	832644	2	· Bearing sleeve		
40	943869	X	· Shim		TH = 0,05 MM
	946179	X	· Shim		TH = 0.10mm
	943870	X	· Shim		TH = 0.20mm
41	967352	X	· Shim		TH = 0,05 MM
	943866	X	· Shim		TH = 0.10mm
	943867	X	· Shim		TH = 0.20mm
	943868	X	· Shim		TH = 0.40 mm
42	897385	1	· Shaft		
43	814601	1	· Sliding sleeve		
			Bulletin P-44-1-8	P-44-1-8-EN	Shift mechanism, shift cone and shoe
			Bulletin P-44-1-18	P-44-1-18-EN	Shift Cone
44	813970	1	· Spring		
45	26411	1	· Shim		
46	951077	1	· Snap ring		
47	181359	4	· Needle roller assemb		

REF	PART NO.	QTY	DESCRIPTION	SEE SEC.	NOTES
48		2	· Spacer ring		
49	897313	1	· Spacer ring		
50	897312	2	· Lock ring		
51	839332	1	· Nut		TH = 2,00 MM
	839333	1	· Nut		TH = 2,37 MM
	839334	1	· Nut		TH = 2,65 MM
52	839504	1	· Shift mechanism		
53	839505	1	· · Bearing housing		
54	897816	1	· · Eccentric piston		
			Bulletin P-44-1-7	P-44-1-7-EN	Shift mechanism, eccentric piston
55	814603	1	· · Dog		
56	814184	1	· · Spring		
57		2	· · Ball		PZ-2829528
58		2	· · Spring		PZ-2829528
59		X	· · Locking wire		PZ-2829528 L = 300 MM
60	897711	1	· · Screw		
61	897871	X	· · Shim		TH = 0.2mm
62	958838	1	· · Sealing ring		
63	951924	1	· · Spring pin		
64	942871	1	· · Clevis pin		
65	925093	1	· · O-ring		
66	940169	4	· Hexagon screw		
67	875826	1	· Bellows kit		
68	853013	1	· · Hose clamp		
69	853012	1	· · Hose clamp		
70	839351	1	· Oil dipstick		
71	955974	1	· O-ring		
72		1	· Sign		
73	804269	2	· Drive screw		
74	832570	1	Protecting cover		INCLUDED IN COMPLETE AQ 290 DRIVE UNIT 853451., INCLUDED IN COMPLETE AQ 290 DRIVE UNIT 853459.
75	897873	1	· Latch		
76	943218	1	· Cross recessed screw		
77	941816	1	Cross recessed screw		INCLUDED IN COMPLETE AQ 290 DRIVE UNIT 853451., INCLUDED IN COMPLETE AQ 290 DRIVE UNIT 853459.
78	853031	1	Sign		INCLUDED IN COMPLETE AQ 290 DRIVE UNIT 853451., INCLUDED IN COMPLETE AQ 290 DRIVE UNIT 853459., P
	853030	1	Sign		INCLUDED IN COMPLETE AQ 290 DRIVE UNIT 853451., INCLUDED IN COMPLETE AQ 290 DRIVE UNIT 853459., S.B
79	853029	1	Sign		INCLUDED IN COMPLETE AQ 290 DRIVE UNIT 853451., INCLUDED IN COMPLETE AQ 290 DRIVE UNIT 853459.