



Parts Catalog - Option Detail

| 08.11 Sv F 855, NT495, NT743, N mine inc 11 | w100gd NTA855 N106 | F | 15-OCT-91 |
|--|-----------------------|-----|-----------|
| mins inc 12 | | | |
| 12 | | | |
| | | ±11 | |
| 1 | | | |
| | | | 8 9 |
| | | | |

SMALL | MEDIUM | LARGE

| Cart | Ref No | Part Number | Part Description | Required | Remarks | |
|--------------|--------|-------------|---------------------------------------|----------|-----------------------------------|--|
| View My Cart | | | | | | |
| | | SW1005 | Raw Water Pump | | Jabsco light duty raw water(More) | |
| | | i | i i i i i i i i i i i i i i i i i i i | | | |

| | | | | pump. Model 7420-0101 with |
|----|---------|------------------------|---|-------------------------------|
| | | | | 5.5foot (1.68M) lift |
| | | | | capability at 54GPM |
| | | | | (204/liter/min) against |
| | | | | maximum, against a discharge |
| | | | | head of 54foot (16.46M) at |
| | | | | 1800RPM. Not available for |
| | | | | 1500RPM due to pump flow |
| | | | | limitation. |
| 1 | 178691 | V Belt | 1 | |
| 2 | 3010343 | Sea Water Pump Pulley | 1 | |
| 3 | S 103 D | Hexagon Head Cap Screw | 4 | 3/8 - 16 x 1 1/4 in. |
| 4 | S 223 | Heavy Hexagon Nut | 4 | 3/8 - 16 UNC |
| 5 | 108330 | Plain Washer | 4 | 3/8 in. |
| 6 | 3018208 | Plain Hose Coupling | 2 | |
| 7 | 3278137 | Sea Water Pump | 1 | |
| 8 | S 109 | Hexagon Head Cap Screw | 3 | 3/8 - 16 x 7/8 in. |
| 9 | S 604 | Lock Washer | 3 | 3/8 in. |
| 10 | 3010337 | Sea Water Pump Bracket | 1 | |
| 11 | 43828 D | Hose Clamp | 4 | 2 1/16 - 3 in. |
| 12 | 67185 | Plain Hose | 2 | |
| 13 | 3010339 | Water Transfer Tube | 1 | |
| | 146892 | Minor Service Kit | | Includes impeller, seals, |
| | | | | gaskets, and screws. |
| | 3278360 | Major Service Kit | | Includes minor service kit |
| | | | | and all remaining serviceable |
| | | | | parts. |

© 2019 Cummins Inc., Box 3005, Columbus, IN 47202-3005 U.S.A. Terms of Use and Disclaimers | Recommended System Requirements Need Assistance? Please click on the Contact Us button in the top right corner of any page.